

LINEAR LED HIGH BAY



APPLICATIONS

- Indoor Lighting
- Offices
- Warehouses
- Industrial & Manufacturing Spaces

FEATURES

- Die-formed cold-rolled steel housing
- Eco-frame & full body linear construction
- High lumen efficiency and high CRI
- UL 2459/CSA 182.3 power connector included
- V hook & hanging chain included
- ETL / cETL Listed
- DesignLights Consortium Listed (DLC)
- 10 year warranty
- Optional occupancy sensor available

Option 1: on/off occupancy sensor
Option 2: bi-level dimming with occ sensor



| Type | Model | Voltage | Frequency | Watts | Lumens (Min) | Lumens (Nominal) | Color | CRI | Dimensions |
|-----------|---------------|-----------|-----------|-------|--------------|------------------|-------|-----|----------------------|
| Eco-Frame | HB5D-110 (4K) | 120v-277v | 50-60 Hz | 110W | 10800 | 12600 | 4000K | >80 | 21.5" x 11.8" x 2.4" |
| Eco-Frame | HB5D-110 (5K) | 120v-277v | 50-60 Hz | 110W | 11550 | 12650 | 5000K | >80 | 21.5" x 11.8" x 2.4" |
| Eco-Frame | HB6D-160 (4K) | 120v-277v | 50-60 Hz | 160W | 16328 | 18900 | 4000K | >80 | 21.5" x 16.0" x 2.4" |
| Eco-Frame | HB6D-160 (5k) | 120v-277v | 50-60 Hz | 160W | 16800 | 18900 | 5000K | >80 | 21.5" x 16.0" x 2.4" |
| Eco-Frame | HB8D-220 (4k) | 120v-277v | 50-60 Hz | 220W | 21986 | 24900 | 4000K | >80 | 43.0" x 10.4" x 3.4" |
| Eco-Frame | HB8D-220 (5K) | 120v-277v | 50-60 Hz | 220W | 23100 | 24955 | 5000K | >80 | 43.0" x 10.4" x 3.4" |



| Type | Model | Voltage | Frequency | Watts | Lumens (Min) | Lumens (Nominal) | Color | CRI | Dimensions |
|-----------|---------------|-----------|-----------|-------|--------------|------------------|-------|-----|----------------------|
| Full Body | HB7D-110 (4K) | 120v-277v | 50-60 Hz | 110W | 11103 | 12600 | 4000K | >80 | 43.0" x 10.4" x 3.4" |
| Full Body | HB7D-110 (5K) | 120v-277v | 50-60 Hz | 110W | 11500 | 12650 | 5000K | >80 | 43.0" x 10.4" x 3.4" |
| Full Body | HB7D-160 (4K) | 120v-277v | 50-60 Hz | 160W | 15996 | 18900 | 4000K | >80 | 43.0" x 10.4" x 3.4" |
| Full Body | HB7D-160 (5k) | 120v-277v | 50-60 Hz | 160W | 16800 | 18900 | 5000K | >80 | 43.0" x 10.4" x 3.4" |

GLOBAL LIGHTING ORGANIZATION



LINEAR LED HIGH BAY



APPLICATIONS

- Indoor Lighting
- Offices
- Warehouses
- Industrial & Manufacturing Spaces

FEATURES

- Die-formed cold-rolled steel housing
- Eco-frame & full body linear construction
- High lumen efficiency and high CRI
- UL 2459/CSA 182.3 power connector included
- V hook & hanging chain included
- ETL / cETL Listed
- DesignLights Consortium Listed (DLC)
- 10 year warranty
- Optional occupancy sensor available

Option 1: on/off occupancy sensor
Option 2: bi-level dimming with occ sensor



| Type | Model | Voltage | Frequency | Watts | Lumens (Nominal) | DLC Premium | Color | CRI | Dimensions |
|-----------|------------------|-----------|-----------|-------|------------------|-------------|-------|-----|----------------------|
| Eco-Frame | HB5D-110-HE (4K) | 120v-277v | 50-60 Hz | 110W | 12990 | Yes | 4000K | >80 | 21.5" x 11.8" x 2.4" |
| Eco-Frame | HB5D-110-HE (5K) | 120v-277v | 50-60 Hz | 110W | 14680 | Yes | 5000K | >80 | 21.5" x 11.8" x 2.4" |
| Eco-Frame | HB6D-160-HE (4K) | 120v-277v | 50-60 Hz | 160W | 19450 | Yes | 4000K | >80 | 21.5" x 16.0" x 2.4" |
| Eco-Frame | HB6D-160-HE (5k) | 120v-277v | 50-60 Hz | 160W | 22020 | Yes | 5000K | >80 | 21.5" x 16.0" x 2.4" |
| Eco-Frame | HB8D-220-HE (4k) | 120v-277v | 50-60 Hz | 220W | 26040 | Yes | 4000K | >80 | 43.0" x 10.4" x 3.4" |
| Eco-Frame | HB8D-220-HE (5K) | 120v-277v | 50-60 Hz | 220W | 29370 | Yes | 5000K | >80 | 43.0" x 10.4" x 3.4" |



| Type | Model | Voltage | Frequency | Watts | Lumens (Nominal) | DLC Premium | Color | CRI | Dimensions |
|-----------|------------------|-----------|-----------|-------|------------------|-------------|-------|-----|----------------------|
| Full Body | HB7D-110-HE (4K) | 120v-277v | 50-60 Hz | 110W | 13275 | Yes | 4000K | >80 | 43.0" x 10.4" x 3.4" |
| Full Body | HB7D-110-HE (5K) | 120v-277v | 50-60 Hz | 110W | 14680 | Yes | 5000K | >80 | 43.0" x 10.4" x 3.4" |
| Full Body | HB7D-160-HE (4K) | 120v-277v | 50-60 Hz | 160W | 19275 | Yes | 4000K | >80 | 43.0" x 10.4" x 3.4" |
| Full Body | HB7D-160-HE (5k) | 120v-277v | 50-60 Hz | 160W | 22020 | Yes | 5000K | >80 | 43.0" x 10.4" x 3.4" |

GLOBAL LIGHTING ORGANIZATION



RoHS

